

FT USA V2 Cremator



FT USA V2 Cremator

- ✔ Low price, high quality
- ✓ Short installation time
- ✓ Compact and quiet
- **✓** Fully automatic
- ✓ Excellent environmental performance
- ✓ Low maintenance, with easy access to components



FT USA V2

Specifications		
·		
Height:	9' 7" (115")	
Width:	5' 4" (64")	
Length:	14' 3"	
Weight:	25,000 lbs	
Fuel:	Natural gas / LPG	
Opening for installation:	8' wide x 10' high	
Capacity:	Up to 500 cremations per year	
Average cremation time:	90 minutes	

Electrical Characteristics	
Combustion air fan:	1.200 cu.ft/min at 68°F, 5.0 HP
Control system:	1.5 kW
Electrical supply:	60 A service 208-230 V, 60 Hz, 1 phase, 4 wire (2 line, 1 ground, 1 neutral)

Fuel consumption	
Burner ratings: • Primary Burner: • Secondary Burner:	• 750,000 Btu/hr • 1,250,000 Btu/hr
Natural Gas usage typically	12 cu.ft/min at 8" Water gauge (excludes pre-heating of cremator)
LPG usage on request	

Your continuity is our priority! Worldwide...

Standard and bespoke solutions efficiently implemented! FT supplies state-of-the-art systems across the globe that meet the most stringent environmental requirements. Reliability, innovation, sustainability, cost efficiency and safety are our core values. Our clients can rely on us throughout the whole process including 24/7 after installation is complete. Your continuity is always our priority. Hundreds of satisfied clients make FT the proud market leader in the field of design, construction and maintenance of cremation, filtration and incineration equipment.



FT The Americas

940 Lake Road | Medina OH 44256 | USA Phone: +1 330 723 63 39 / +1 888 883 28 76 | Fax: +1 330 723 58 41 | info.usa@facultatieve-technologies.com

FT The Americas • FT The Netherlands • FT United Kingdom • FT Germany • FT France • FT Czech Republic FT is part of 'the Facultatieve Group'